

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
29 November 2001 (29.11.2001)

PCT

(10) International Publication Number
WO 01/90901 A2

- (51) International Patent Classification⁷: **G06F 12/12**
- (21) International Application Number: PCT/US01/17050
- (22) International Filing Date: 25 May 2001 (25.05.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/207,125 25 May 2000 (25.05.2000) US
- (71) Applicant: **EXENT TECHNOLOGIES, INC.** [US/US];
6903 Rockledge Drive, 15th floor, Bethesda, MD 20817 (US).
- (72) Inventor: **ROMM, Amnon**; 131 Grenadier Crescent,
Thornhill, Ontario, L4J 7V7 (CA).
- (74) Agent: **WORTH, Gerald, E.**; Testa, Hurwitz & Thibault,
LLP, High Street Tower, 125 High Street, Boston, MA
02110 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— *without international search report and to be republished upon receipt of that report*
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*



WO 01/90901 A2

(54) Title: DISK CACHING

(57) Abstract: A method of caching information between work sessions for future use is described. The method efficiently determines those blocks of information least likely to be required for future use and preferentially discards such blocks from the cache when additional cache storage space is needed. The method also provides for the dynamic allocation of cache space between work sessions of different content.

DISK CACHING

RELATED APPLICATIONS

- 10 This application claims the benefit of U.S. Provisional Application No. 60/207,125, filed May 25, 2000.

FIELD OF THE INVENTION

- 15 This technology relates generally to a method for caching information on the hard drive of a client computer. More particularly, the technology relates to a method for the caching of information between work sessions to increase the local accessibility of blocks of information.

20 BACKGROUND

- Client computers are used to execute program software for many purposes. The software executed can comprise many different applications and types of content. Examples of content include any windows-based software, games, various applications, or any software that utilizes the file system of the client computer and employs session-based caching. Content can be executed on clients that utilize a variety of operating systems and hardware configurations. Content can be accessed many different times over the course of one or more work sessions.

- A client computer requires blocks of information for the content to operate properly. The blocks of information can come from different data sources, such as a compact disk (CD), a DVD, or from another computer such as a file server. The client computer can be connected to the file server by a local network (LAN) or a wide area network (WAN), such as the Internet.

- Generally, content must be installed on a client computer before it can be executed. It is generally installed from a data source, such as those listed above. During

5 the installation process, files of a certain size that are frequently required for operation of the content are copied to the hard drive of the client computer. From there they are readily accessible. Since the hard drive of the client computer is generally limited in storage capacity, some of the large content files may not be copied to it. These large files could comprise, for example, video files, large executable files, or Dynamic Link
10 Libraries. When they are needed these large content files must then be retrieved from the data source, which has a slower retrieval time. Alternatively, if only a portion of a large content file is to be used, the blocks of information representing this portion of the file can be cached on the hard drive of the client computer.

After installation, a work session can be started to commence use of the content.
15 During the work session additional blocks of information are required. Some blocks of information are used more frequently than other blocks. The blocks of information can be obtained directly from the data source of the content if it is still available during the work session, although access times to this information are generally constrained. The slow response times are generally caused by the various technical and hardware
20 limitations of the data source being used.

Conversely, the access time to blocks of information stored on the hard drive of a client computer is comparatively fast. However, the hard drive of a client computer may possess only limited storage capacity. For these reasons, the hard drive of the client computer is the preferred storage location for blocks of frequently accessed information
25 that are of manageable size.

To reduce the impact of these limitations, various caching methods are used to optimize accessibility to the blocks of information required by the content of an active work session. A certain amount of storage space is set aside on the hard drive of the client computer for each content. As the content is used, blocks of information brought
30 to the client computer from the data source are temporarily stored (cached) in this allocated space on the hard drive. As the space fills and new information needs to be stored, the oldest information is discarded to make room for the new. By this means faster repeated access can be provided to blocks of information that have been most recently used. Ultimately, when the work session using this content on the client
35 computer is completed, the allocated space that was used on the hard drive is made

5 available for use for other purposes. Unfortunately, the next time a work session is commenced for the same content, the blocks of information that had been cached are no longer available and need to be obtained again from the data source. This results in inefficiency and delays, and diminishes the overall experience of the operator of the client computer.

10 What is needed is an improved method of caching blocks of information on a local client computer that reduces information transfer requirements from the data source, thereby improving the responsiveness of the client computer.

SUMMARY OF THE INVENTION

15 The present invention features a method for caching blocks of information on a client computer to address the preceding problems. In one aspect, the invention provides for the caching of blocks of information in an allocated storage space on the hard drive of a client computer. Access frequency information is stored for each block of information cached and is used to calculate a discard priority for the stored block. When an incoming
20 block of information needs to be stored, storage space in the cache is made available for it by discarding blocks of information based on their calculated discard priority.

Another embodiment of the invention provides for the dynamic allocation of storage space on the computer between different caches. The dynamic allocation can reassign storage space from the cache of an inactive work session to that of an active
25 work session or from the cache of an active work session to that of another active work session. The storage space to be reassigned is determined based upon block discard priority.

In another embodiment of the invention, the size of the allocated storage space for the work session can be changed. Reduction of the allocated storage space is performed
30 by discarding blocks of information, based on their discard priority.

In yet another embodiment of the invention, the cached blocks of information are not discarded at the end of a work session, but are retained for use in a subsequent work session. In yet another embodiment, the access frequency information used to determine the discard priority of a block is determined using the number of times the block has been
35 accessed in the present work session, in a prior work session, in a plurality of prior work

5 sessions, of some combination. The discard priority determination can also be adjusted based on the amount of time since it has been most recently accessed.

Another aspect of the invention features a method for caching blocks of information on the hard drive of a client computer employing multiple work sessions. Storage space is allocated on a client computer for the cache of each active work session. 10 Blocks of information are then stored in the storage space of each cache. Access frequency information is stored for each block of information cached, and is used to calculate a discard priority for each stored block. When an incoming block of information needs to be stored, storage space is provided for the new block by discarding stored blocks of information from any of the active work sessions. The blocks to be 15 discarded are determined based upon their calculated discard priority.

Another embodiment of the invention provides storage space for the incoming block of information by discarding blocks of information from the cache of an inactive work session to that of an active work session, or from the cache of an active work session to that of another active work session. The storage space to be reassigned is 20 determined based upon block discard priority.

In another embodiment of the invention, the cached blocks of information are not discarded at the end of a work session, but are retained for use in a subsequent work session. Another embodiment of the invention allows the size of the allocated storage space for a work session can be changed. Reduction of the allocated storage space is 25 performed by discarding blocks of information, based on their discard priority.

In yet another embodiment, the access frequency information used to determine the discard priority of a block is determined using the number of times the block has been accessed in the present work session, in a prior work session, in a plurality of prior work sessions, or some combination. The discard priority determination can also be adjusted 30 based on the amount of time since it has been most recently accessed.

Yet another aspect of the invention features a method for caching blocks of information on a client computer. Blocks of information are cached in the storage space of a client computer. Access frequency information is stored for each block of information cached, and is used to calculate a discard priority for the stored block. When 35 an incoming block of information needs to be stored, storage space in the cache is made

5 available for it by discarding blocks of information based on their calculated discard priority.

An embodiment of the invention provides for the dynamic allocation of the storage space used to cache the blocks of information. The access frequency information used to determine the discard priority of a block is determined using the number of times
10 the block has been accessed in the present work session, in a prior work session, in a plurality of prior work sessions, or some combination. The discard priority determination can also be adjusted based on the amount of time since it has been most recently accessed.

15 BRIEF DESCRIPTION OF THE DRAWING

These and other features of the invention are more fully described below in the detailed description and accompanying drawing.

Figure 1 is a block diagram illustrating the sequence of steps used to cache a block of information, in accordance with the method of this invention.

20

DETAILED DESCRIPTION

The present invention provides for the efficient caching of blocks of information on the hard drive of a local client computer. One aspect of the invention features a Least Recently Least Frequently Used (LRLFU) method for efficient caching. Figure 1 is a
25 block diagram illustrating the sequence of steps used to cache a block of information, in accordance with the method of this invention.

A storage space is allocated to provide a cache in memory (e.g., the hard drive) for cached blocks of information to be stored on the client computer. In one embodiment, the storage space is allocated occur prior to the caching of the first block of
30 information. In another embodiment, the storage space is allocated simultaneously with the caching of the first block of information.

When a block of information is to be stored (step 10), the cache (or storage space) is checked to determine whether sufficient memory space exists for the block (step 15). If there is sufficient space, the block is stored for use (step 20) and the method is finished

5 for that block. If there is not sufficient room in the cache to store the block, the block
with the highest discard priority is identified (step 25). A determination is made as to
whether removal of the block with the highest discard priority will provide sufficient
space to store the incoming block (step 30). If insufficient space is available, the block of
information with the next-highest discard priority is identified (step 35), and the amount
10 of storage space to be provided by removal of both of these blocks is calculated (step 40).
The cycle of steps 30, 35, and 40 is repeated until sufficient storage space is identified for
the incoming block. The block is then stored (step 45) replacing the blocks identified
above, and its discard priority calculated (step 50). The listing of the blocks is then
sorted in order of descending discard priority (step 55). This process is repeated for each
15 subsequent block of information to be cached.

A more particularized description of these method steps is found in the paragraphs
that follow, including samples of underlying mathematical calculations that can be used
to calculate the discard priority.

In addition, blocks of information for various content that employ multiple
20 sequential work sessions. Blocks of information are retained in a cache on the hard drive
of the local client computer, based on the likelihood of their being used in the future.
This reduces the number of retrieval operations required to obtain these blocks of
information from other data sources. Reducing the retrieval requirements from these
slower sources results in improved efficiency, faster responses, and an enhanced user
25 experience for the operator of the client computer.

Another feature of the LRLFU method is that blocks of information cached for a
given content are not discarded at the end of the work session. Rather than abandoning
the blocks of information cached for a content at the conclusion of a work session, the
cache contents are retained. They are then available for a subsequent work session using
30 the same content, provided the prior work session has finished. This persistent caching of
blocks of information reduces the amount of information a subsequent work session will
need to obtain from the data source. The eventual elimination of the persistently cached
blocks does not occur until their discard priority becomes sufficiently high to warrant
replacing them with different blocks of information.

5 The discard priority of each block is used to determine which of them are least likely to be required in the future. When additional space for a new block of information is needed in the cache, the LRLFU method discards the block with the highest discard priority to make room for the new block. The block discarded can be from the cache of the present work session, the cache of an inactive work session of a different content, or
10 from the cache of a concurrently active work session of a different content.

 Determination of the discard priority for each block of information contained in a cache represents an important aspect of this invention. Its determination is predicated on some general assumptions. When calculating the discard priority for a block of information, it is likely that if that block was required in a prior work session, it will also
15 be needed in a subsequent work session of the same content. Accordingly, continued caching of this block of information on the hard drive of the client computer reduces the likelihood of having to obtain it from a different and slower source in the future. Likewise, a block of information should be assigned a lower discard priority if it is accessed multiple times during a work session. Frequent access to the block during the
20 current work session or prior work sessions is an indication it will be frequently accessed in the next work session of that content. Finally, if the prior work session was chronologically close in time to the present session, the common range of information used by the two sessions is likely to be larger. Calculation of the block discard priority reflects these assumptions.

25 For calculation of the discard priority of a block, the cache for the work session of content comprises several attributes. First, storage space is allocated to provide for the existence of the cache in memory (e.g., the hard drive of the client computer) as described above. Moreover, the cache has a specific size initially, although the size of the cache for different contents can vary. However, the cache size of each work session
30 can be dynamically adjusted. After the cache has become full, a new block of information is written to the storage location of the cached block with the highest discard priority, effectively deleting the old block. The block deleted may have been stored for the present work session, the work session of content that is now inactive, or the active work session of another content. The block to be deleted is selected based on its discard

5 priority. This provides for the dynamic adjustment of the cache space available for each content being used, based on the discard priority calculation results.

Dynamic adjustment of the amount of storage space allocated to a cache may also be achieved by manual intervention. For example, if a user wishes to decrease the amount of storage space allocated for a cache, the LRLFU method removes sufficient
10 blocks of information from the cache to achieve the size reduction. The blocks to be removed are determined based upon their discard priority, thereby preserving within the cache the blocks most likely to be used in the future.

In addition to the size of the cache, the Global Reference Number and the Head-of-the-List block identification location represent two more attributes of the cache for
15 each work session. The Global Reference Number is reset to zero each time a work session is started, and is incremented by one each time the cache is accessed. The Head-of-the-List block identification location indicates the identity of the block in the cache of the work session that possesses the highest discard priority. In other embodiments of the invention, it can be used to indicate the identity of the block with the highest discard
20 priority as selected from the current work session, any inactive work sessions, and/or any other active work sessions.

Likewise, each block contained within the cache of a work session has certain attributes that are used in calculating its discard priority. Each block has associated with it (for example, as an array) a Reference Number, plus up to m entries in its Reference
25 Count array. The Reference Number of a block is set equal to the value of the Global Reference Number each time that block is accessed. This value is stored as the Reference Number of that block. The block Reference Numbers can be used to sort them in the order in which they have been accessed.

The m entries of the Reference Count array for each block represent the number
30 of times that block was accessed in each of the previous m work sessions. The present session is identified as session 0, the prior session is identified as session 1, and so forth. Up to m entries in the Reference Count array are stored for a given block. The value stored in the Reference Count array for each session represents how many times that block was accessed during that session. By using the Reference Number and the

- 5 Reference Count array values for a given block, its discard priority can be calculated as discussed below.

Initialization of the above-identified parameters is performed as follows. When the client computer is booted up, the Reference Number and Reference Count array values are set to zero. When a work session is started, the Global Reference Number for that cache is set to zero, and the Reference Count values for each block in the array are shifted one place to the right, discarding the oldest values at position $m-1$ (the position 10 that is assigned to session m). The Reference Count values for session 0 (the present session) start at zero and are incremented by one each time the block is accessed.

- These values are used by the LRLFU method to calculate the discard priority.
- 15 The discard priority of a block is calculated each time it is accessed. After the Discard Priority has been calculated, the list of blocks is sorted in descending order based on the discard priority calculated. The block with the highest discard priority is at the top of the sorted list, and its identity is indicated in the Head-of-the-List block identification location. It is the first block to be discarded when additional space is required in the 20 cache.

The discard priority of a block is determined based on a calculated weighted time factor (Tw) and a weighted frequency factor (Fw). They are used as follows:

$$\text{Block Discard Priority} = N1 * 1 / ((1 + Tw) * Fw)$$

25

and calculated by the following formulae:

$$Tw = P1 * (\text{Block Reference number} / \text{Global Reference Number})$$

30

$$Fw = P2 * \sum_m (\text{RefCount}[m] / 2^m)$$

In these equations, $N1$ represents a normalization factor and is set to a fixed value that causes the result of the equation to fall within a desired numerical range. $P1$ and $P2$ are weighting factors. They are used to proportion the relative weight given to the

5 frequency factor (Fw) as compared with the time factor (Tw), to achieve the desired results.

The time factor (Tw) is proportional to the time of last access of the block within the work session. If the block has not been accessed during the current work session, the time factor is zero. If the block was recently accessed, the time factor has a value
10 approaching P1 times unity.

The frequency factor (Fw) represents the number of times the block has been accessed during the current session (session number 0) through the m th session (session number $m-1$). These are summed up and discounted based on the age of the prior work session(s). In the above equation, the discounting is performed by the factor 2^m , where m
15 represents the session number corresponding to the Reference Count array value for that block of information. Other discounting factors can be used for this purpose. Greater discounting of older work session Reference Count array data can be accomplished by using factors such as 2^{2m} , or 2^{mm} , etc., in place of 2^m . Alternatively, discounting of the older work session Reference Count array data could be reduced, for example, by using a
20 discounting factor of 1.5^m or the like, in place of 2^m , thereby more strongly emphasizing the Reference Count array values of the older work sessions for each block.

Block Discard Priorities can be calculated using the results of the above calculations. These are calculated for a block of information each time it is accessed from the cache. After the discard priority has been calculated, the listing of the blocks is
25 resequenced and the block with the highest discard priority is positioned at the top of the list. The identity of this block is placed in the Head-of-the-List block identification location. It then becomes the next block to be discarded when additional cache space is required. Should the space required for the incoming block of information be greater than what was freed up, then the block of information with the next highest discard
30 priority is also discarded, and so on. By this method sufficient room is created for the incoming block of information.

Operating in this manner, the LRLFU method provides for efficient utilization of the storage space allocated for the caching of blocks of information for a given work session of a content. This is done by discarding the block with the highest discard
35 priority, as calculated by the LRLFU method, to methodically create room for the new

5 blocks to be cached for the ongoing work session. The blocks discarded are those least likely to be needed in the future, based on when they were last accessed and how often they have been used in prior work sessions. At completion of the work session the cache is not cleared, but the blocks of information and their corresponding priority information are retained for use with subsequent work sessions of that content. Since the cache is not
10 cleared at the termination of the work session, the method also provides for the persistent storage of the blocks of information most likely to be needed by present or future work sessions of a given content. This results in improved performance, increased efficiency, and an enhanced user experience.

By utilizing the above method and adjusting the parameters identified and
15 explained, improved utilization of the hard drive space available for caching can be performed.

While the invention has been particularly shown and described with reference to specific preferred embodiments, it should be understood by those skilled in the art that various changes in form and detail may be made therein without departing from the spirit
20 and scope of the invention as defined by the appended claims.

What is claimed is:

- 1 1. A method for caching blocks of information for content utilized by a client computer in
2 multiple sequential work sessions, the method comprising:
 - 3 a) caching blocks of information in allocated storage space on a hard drive of the
4 client computer;
 - 5 b) storing, for each block of information, a first parameter corresponding to the
6 frequency at which such block of information has been accessed by the client
7 computer;
 - 8 c) determining a discard priority value for each block of information using the
9 first parameter; and
 - 10 d) discarding stored blocks of information from the storage space based upon their
11 discard priority value to create additional room for new blocks of information in
12 the storage space.
- 1 2. The method of claim 1 wherein step a) further comprises dynamically allocating
2 storage space on the hard drive of the client computer.
- 1 3. The method of claim 1 wherein step a) further comprises dynamically allocating
2 storage space on the hard drive of the client computer by reassigning storage space from
3 an inactive work session to an active work session.
- 1 4. The method of claim 1 wherein step a) further comprises dynamically allocating
2 storage space on the hard drive of the client computer by reassigning storage space from
3 an active work session to another active work session.
- 1 5. The method of claim 1 further comprising e) changing the size of the allocated storage
2 space for the work session.

1 6. The method of claim 1 further comprising e) reducing the size of the allocated storage
2 space for the work session by discarding blocks of information based upon their discard
3 priority value.

1 7. The method of claim 1 further comprising:

2 e) retaining cached blocks of information at the end of a work session for use in a
3 subsequent work session.

1 8. The method of claim 1 wherein step b) further comprises determining the first
2 parameter for each block of information based on at least one of the number of times the
3 block has been accessed during the current work session, the number of times the block
4 was accessed in a prior work session, or the number of times the block was accessed in a
5 plurality of prior work sessions.

1 9. The method of claim 1 wherein step b) further comprises determining the first
2 parameter for each block of information based on at least one of the number of times the
3 block has been accessed during the current work session, the number of times the block
4 was accessed in a prior work session, or the number of times the block was accessed in a
5 plurality of prior work sessions, and step c) further comprises determining the discard
6 priority value for each block of information based on at least one of the first parameter or
7 a number of access cycles of the cache since which the block of information has been
8 used.

1 10. A method for caching blocks of information on the hard drive of a client computer,
2 the method comprising:

3 a) allocating storage space on a hard drive of the client computer for each active
4 work session;

5 b) caching the blocks of information for each active work session in the allocated
6 storage space;

- 7 c) storing, for each block of information, a first parameter corresponding to the
8 frequency at which each such block of information has been accessed by the
9 client computer;
- 10 d) determining a discard priority value for each block of information using the
11 first parameter;
- 12 e) discarding stored blocks of information from the storage space of each work
13 session based upon their discard priority value, to provide additional storage space
14 for new blocks of information for each such active work session on the hard drive
15 of the client computer.
- 1 11. The method of claim 10 wherein step e) further comprises discarding stored blocks of
2 information from the storage space of an inactive work session.
- 1 12. The method of claim 10 wherein step e) further comprises discarding stored blocks of
2 information from the storage space of another active work session.
- 1 13. The method of claim 10 further comprising:
- 2 f) retaining cached blocks of information at the end of a work session for use in a
3 subsequent work session.
- 1 14. The method of claim 10 further comprising f) changing the size of the allocated
2 storage space for one of the active work sessions.
- 1 15. The method of claim 10 further comprising f) reducing the size of the allocated
2 storage space for one of the active work sessions by discarding blocks of information
3 based upon their discard priority value.
- 1 16. The method of claim 10 wherein step c) further comprises determining the first
2 parameter for each block of information based on at least one of the number of times the
3 block has been accessed during the current work session, the number of times the block
4 was accessed in a prior work session, or the number of times the block was accessed in a
5 plurality of prior work sessions.

1 17. The method of claim 10 wherein step c) further comprises determining the first
2 parameter for each block of information based on at least one of the number of times the
3 block has been accessed during the current work session, the number of times the block
4 was accessed in a prior work session, or the number of times the block was accessed in a
5 plurality of prior work sessions, and step d) further comprises determining the discard
6 priority value for each block of information based on at least one of the first parameter or
7 a number of access cycles of the cache since which the block of information has been
8 used.


1 18. A method for caching blocks of information for content utilized by a client computer
2 in multiple sequential work sessions, the method comprising:

- 3 a) caching blocks of information in allocated storage space on the client
4 computer;
- 5 b) storing, for each block of information, a first parameter corresponding to the
6 frequency at which such block of information has been accessed by the client
7 computer;
- 8 c) determining a discard priority value for each block of information using the
9 first parameter; and
- 10 d) discarding stored blocks of information from the storage space based upon their
11 discard priority value to create additional room for new blocks of information in
12 the storage space.

1 19. The method of claim 18 wherein step a) further comprises dynamically allocating the
2 storage space, and step b) further comprises determining the first parameter for each
3 block of information based on at least one of the number of times the block has been
4 accessed during the current work session, the number of times the block was accessed in
5 a prior work session, or the number of times the block was accessed in a plurality of prior
6 work sessions.

- 1 20. The method of claim 18 wherein step a) further comprises dynamically allocating the
- 2 storage space, step b) further comprises determining the first parameter for each block of
- 3 information based on at least one of the number of times the block has been accessed
- 4 during the current work session, the number of times the block was accessed in a prior
- 5 work session, or the number of times the block was accessed in a plurality of prior work
- 6 sessions, and step c) further comprises determining the discard priority value for each
- 7 block of information based on at least one of the first parameter or a number of access
- 8 cycles of the cache since which the block of information has been used.

1/1

**Figure 1**

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
29 November 2001 (29.11.2001)

PCT

(10) International Publication Number
WO 01/90901 A3

- (51) International Patent Classification⁷: G06F 12/12
- (21) International Application Number: PCT/US01/17050
- (22) International Filing Date: 25 May 2001 (25.05.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/207,125 25 May 2000 (25.05.2000) US
- (71) Applicant: EXENT TECHNOLOGIES, INC. [US/US];
6903 Rockledge Drive, 15th floor, Bethesda, MD 20817
(US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW). Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM). European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR). OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
- (72) Inventor: ROMM, Amnon; 131 Grenadier Crescent,
Thornhill, Ontario, L4J 7V7 (CA).
- (88) Date of publication of the international search report:
21 March 2002
- (74) Agent: WORTH, Gerald, E.; Testa, Hurwitz & Thibault,
LLP, High Street Tower, 125 High Street, Boston, MA
02110 (US).
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*



WO 01/90901 A3

(54) Title: DISK CACHING

(57) Abstract: A method of caching information between work sessions for future use is described. The method efficiently determines those blocks of information least likely to be required for future use and preferentially discards such blocks from the cache when additional cache storage space is needed. The method also provides for the dynamic allocation of cache space between work sessions of different content.

INTERNATIONAL SEARCH REPORT

International Application No
PC1/US 01/17050

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 G06F12/12

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97 04393 A (CIRRUS LOGIC INC) 6 February 1997 (1997-02-06) page 5, line 20 -page 6, line 4 page 8, line 6 - line 23 ---	1,2, 7-10,13, 16-20
X	CASTRO M ET AL: "HAC: HYBRID ADAPTIVE CACHING FOR DISTRIBUTED STORAGE SYSTEMS" OPERATING SYSTEMS REVIEW (SIGOPS), ACM HEADQUARTER. NEW YORK, US, vol. 31, no. 5, 1 December 1997 (1997-12-01), pages 102-115, XP000771025 page 104, right-hand column, paragraph 7 -page 106, right-hand column, paragraph 6 --- -/--	1,10,18

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

I later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

8 document member of the same patent family

Date of the actual completion of the international search

7 December 2001

Date of mailing of the international search report

17/12/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

Nielsen, O

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 01/17050

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5 559 984 A (NAKANO HIROHIKO ET AL) 24 September 1996 (1996-09-24) column 2, line 19 -column 3, line 34 ---	1-7, 10-15
Y	EP 0 543 614 A (IBM) 26 May 1993 (1993-05-26) page 2, line 50 -page 3, line 45 -----	1-7, 10-15

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 01/17050

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9704393	A	06-02-1997	US 5829023 A EP 0781431 A1 JP 10513592 T WO 9704393 A1	27-10-1998 02-07-1997 22-12-1998 06-02-1997
US 5559984	A	24-09-1996	JP 3140621 B2 JP 7093205 A	05-03-2001 07-04-1995
EP 0543614	A	26-05-1993	US 5394531 A EP 0543614 A1 JP 2043458 C JP 5225066 A JP 7078768 B	28-02-1995 26-05-1993 09-04-1996 03-09-1993 23-08-1995